

Pre-Made hose assemblies

Gaseco has available a variety of certified and non-certified pressed hose assemblies in different sizes and lengths. Please call for pricing.

High Pressure LP-Gas Hose

Heavy duty braided LP gas hose, flexible in cold weather.

Black neoprene cover resists snagging, abrasion, and weather.

Nitrile tube withstands LP gas permeation. High tensile rayon cord braid designed for 1,750 psi minimum burst. 350 psi maximum working pressure.



Item #	List per	I.D.	OD
1/4" Hose	\$1.24	1/4"	9/16"
3/8" Hose	\$2.62	3/8"	3/4"
1/2" Hose	\$3.26	1/2"	15/16"
3/4" Hose	\$5.70	3/4"	1 1/4"
1" Hose	\$7.08	1"	1 9/16"
1 1/4" Hose	\$12.46	1 1/4"	1 7/8"
1 1/2" Hose	\$16.02	1 1/2"	2 1/16"
2" Hose	\$21.34	2"	2 1/8"
3" Hose	\$32.18	3"	3 3/4"

500'/650' reels for 1/4" and 3/8". 300' to 500' reels for 1/2" through 1". 50' to 60' lengths on 1 1/4" through 2".

SS-25UL Hose for LP Fuel Systems



SS25UL-6

Specially compounded heat resistant synthetic rubber seamless inner tube. Single braid of stainless steel wire. The hose is impregnated with oil and mildew-resistant rubber compound.

Item #	List	Hose ID
SS25UL-4	\$4.06	3/16"
SS25UL-6	\$3.34	5/16"
SS25UL-8	\$3.80	13/32"

Reusable Hose Couplings



206H-4

Reusable, shell and stem type couplings. Needs only a vise and wrench to install. Brass construction through 3/8". Larger sizes are steel. Check OD before ordering.

Item #	List	MNPT Size	Hose ID	Hose OD
206H-4	\$14.54	1/2"	1/2"	15/16"
217H-6	\$18.54	3/4"	3/4"	1 1/4"
226H-8	\$31.16	1"	1"	1 9/16"

Swivel Hose Adapter Union



207-4-4 Female

107-4-4 Male

Rounded nose in swivel end creates a tight metal-to-metal ground joint union.

Straight

Item #	List	Pipe X Pipe Swivel
107-8-8	\$2.98	1/2" M x 1/2" F
107-8-12	\$8.20	1/2" M x 3/4" F
107-12-12	\$4.94	3/4" M x 3/4" F
107-16-16	\$12.46	1" M x 1" F
207-8-8	\$4.46	1/2" F x 1/2" F
207-12-12	\$8.96	3/4" F x 3/4" F
207-16-16	\$10.76	1" F x 1" F


90° Elbow

Item #	List	Pipe X Pipe Swivel
2107-8-8	\$8.14	1/2" M x 1/2" F
2107-12-12	\$10.00	3/4" M x 3/4" F
2107-16-16	\$20.56	1" M x 1" F

45° Elbow

Item #	List	Pipe X Pipe Swivel
3107-8-8	\$9.08	1/2" M x 1/2" F
3107-12-12	\$13.36	3/4" M x 3/4" M
3107-16-16	\$18.48	1" M x 1" M

Couplings For SS25UL Hose



27920-6-6 (90°)

20820-6-6



27720-6-6 (45°)

Item #	List	Hose ID	Connection
20820-4-4	\$2.70	3/16"	Female 1/4" OD Flare
20820-6-6	\$4.02	5/16"	Female 3/8" OD Flare
20820-8-8	\$5.02	13/32"	Female 1/2" OD Flare
22820-8-8	\$7.24	13/32"	1/2" Male Inverted Swivel
27720-6-6	\$10.00	5/16"	Female 3/8" OD Flare(45°)
27720-8-8	\$10.16	13/32"	Female 1/2" OD Flare(45°)
27920-6-6	\$9.58	5/16"	Female 3/8" OD Flare(90°)
27920-8-8	\$11.34	13/32"	Female 1/2" OD Flare(90°)

Boss® Male Clamp Hose Coupling



M3162-20

Versatile, reliable couplings of steel and iron. Safe for use on almost any type of hose service. Each unit receives a coat of electro deposition protection.

Item #	List	Hose ID	Approx Hose OD
M3162-20	\$67.84	1 1/4"	2"
M3162-32	\$90.60	2"	2 3/4"

Standard Brass Hose Ferrule



FBL625

Use with standard hose barb fittings to make permanent connections to hose. Select ferrule I.D. dimension to closely match your hose O.D.

Item #	List	Ferrule I.D.
FBL 575	\$0.32	.575
FBL 600	\$0.32	.600
FBL 625	\$0.32	.625
FBL 650	\$0.32	.650
FBL 675	\$0.34	.675
FBL 775	\$0.34	.775

Carburetion Fitting



HC-8346

Allows hydrostatic relief valve to be installed at the most protected position. The HC-8346 has a 3/8" female flare swivel on the tank valve end. The opposite end is a two piece reusable hose fitting for 5/16" I.D. stainless steel braid L.P.

Item #	List
HC-8346	\$12.60